

Series 537 Insert Plates for Universal PLCC ZIF Test Socket

FEATURES

- Conveniently Hand-insert 7 Separate Insert Plates into 'Live Bug' Universal PLCC ZIF Test Socket (P/N 84-537-21) to hold 7 Differently-sized PLCC Footprints
- · Four Mounting Holes (2 Bifurcated) Mate with Mounting Post in Socket Base for Secure Assembly

GENERAL SPECIFICATIONS

- INSERT: black UL 94V-0 glass-filled Polyphenylene Sulfide (PPS)
- OPERATING TEMPERATURE: -85°F [-65°C] to 500°F [260°C]
- CONTACT BLOCK AND LATCH HINGE: available individually

MOUNTING CONSIDERATIONS

• SUGGESTED PCB HOLE SIZE: $0.035 \pm 0.002 [0.89 \pm 0.05]$ dia.

2.300 [58.42]

2.000 [50.80] CTR



ORDERING INFORMATION

XX-537-20

- Series

Number of Positions (see Table below)

USE **P/N 1110832** WHEN ORDERING ALL SEVEN INSERT PLATES

No. Positions	Dim "A"	Dim. "B"
20	0.395 to 0.397 [10.03 to 10.08]	0.395 to 0.397 [10.03 to 10.08]
28	0.495 to 0.497 [12.57 to 12.62]	0.495 to 0.497 [12.57 to 12.62]
32	0.495 to 0.497 [12.57 to 12.62]	0.595 to 0.597 [15.11 to 15.16]
44	0.695 to 0.697 [17.65 to 17.70]	0.695 to 0.697 [17.65 to 17.70]
52	0.795 to 0.797 [20.19 to 20.24]	0.795 to 0.797 [20.19 to 20.24]
68	0.995 to 0.997 [25.27 to 25.32]	0.995 to 0.997 [25.27 to 25.32]
84	1.195 to 1.197 [30.35 to 30.40]	1.195 to 1.197 [30.35 to 30.40]

2.300 [58.42] SQUARE 2.000 [50.80] CTR 2.000 [50.80] CTR



ALL DIMENSIONS: INCHES [MILLIMETERS] ALL TOLERANCES: ±0.005 [0.13] UNLESS OTHERWISE SPECIFIED FOR TEST SOCKET, SEE <u>DATA SHEET 10010</u> CONSULT FACTORY FOR OTHER SIZES AND CONFIGURATIONS CUSTOMIZATION: ARIES SPECIALIZES IN CUSTOM DESIGN AND PRODUCTION. SPECIAL MATERIALS, PLATINGS, SIZES, AND CONFIGURATIONS CAN BE FURNISHED, DEPENDING ON QUANTITY.

ARIES RESERVES THE RIGHT TO CHANGE PRODUCT GENERAL SPECIFICATIONS WITHOUT NOTICE

PRINTOUTS OF THIS DOCUMENT MAY BE OUT-OF-DATE AND SHOULD BE CONSIDERED UNCONTROLLED



2609 Bartram Road • Bristol, PA 19007-6810 USA TEL 215-781-9956 • FAX 215-781-9845 WWW.ARIESELEC.COM • INFO@ARIESELEC.COM



